CD4232T

42" SLIM BEZEL COMMERCIAL DISPLAY WITH 3M DST TOUCH SCREEN

Interactive digital signage.

ViewSonic's 42" CD4232T Commercial Display features touch screen control powered by 3M's MicroTouch™ DST Touch System. The elegant slim bezel design and dynamic touch panel technology is ideal for use in mall kiosks, corporate directories, product selectors, hotel lobbies, training rooms and point of information applications. The high brightness, high contrast ratio and wide viewing angles clearly communicate your message regardless of ambient light. The fast 8ms response time delivers blur-free scrolling text or video. VGA and RS-232 inputs/outputs allow you to daisy chain multiple displays into your network and still control each display individually. Other inputs include HDMI, S-video, component, composite and PC RGB. The CD4232T with 3M touch screen technology sets a new standard for interactive digital signage displays.

Shown with optional stand.

- Features 3M's MicroTouch™ DST Touch System
- Full HD 1920x1080 panel for vibrant video and crisp images
- 700 nits high brightness and contrast ratio
- RS-232 daisy-chain capable
- VGA and DVI inputs/outputs for flexible connectivity and control
- Remote and panel control lock out
- Installation options include stand or VESA® wall mount
- Integrated ON/OFF scheduling

ViewSonic®
See the difference®

CD4232T 42" SLIM BEZEL COMMERCIAL DISPLAY WITH TOUCH SCREEN

Shown with optional stand.

LCD	Type	42" color TFT active matrix, wide LCD
	Display Area	36.6" horizontal x 20.6" vertical; 42" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	3500:1 (typ)
	Viewing Angles	178° horizontal, 178° vertical
	Response Time	8ms
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	700 cd/m2 (typ)
	Aspect Ratio	16:9
	Panel Surface	Anti-glare, hard coating (3H)
INPUT	Video Input	HDMI, DVI, component, VGA
	Video Output	VGA, component, DVI
	Control Input/Output	RS-232
AUDIO OUTPUT	Speakers	
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	HDMI, DVI
	Power	3-pin plug
POWER	Voltage	AC 100–240V (universal), 50–60Hz
	Consumption	250W (max)
CONTROLS	Panel	Power, Exit, +, –, Menu/Enter
	Picture	Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness
	VGA Setting	Auto adjustment, clock, phase, sharpness, H. position, V. position
	OSD Setting	Languages, OSD H. position, OSD V. position, OSD timer
	Input	VGA, DVI, HDMI, YPbPr, S-video, CVBS (BNC)
	Audio	Volume, mute
	Special	Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset
	Diagnostic	Thermal, back light, ambient, 5V detect, 12 detect
OPERATING CONDITIONS	Temperature (landscape)	32–104°F (0–40°C)
	Temperature (portrait)	41–95°F (5–35°C)
	Humidity	20–80% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand (optional)	37.9" x 23.5" x 6.2" (963mm x 598mm x 157mm)
	Physical without stand	37.9" x 21.8" x 4.3" (961mm x 554mm x 109mm)
WEIGHT	Net with stand (optional)	56.7 lb. (25.7 kg)
	Net without stand	52.0 lb. (23.5 kg)
	Gross without stand	62.0 lb. (28.0 kg)
VESA® MOUNT		400mm x 200mm
REGULATIONS		UL/FCC-B
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS		LCD display, power cable, VGA cable, remote control with batteries, Quick Start Guide
WARRANTY		Three-year limited warranty on parts, labor and backlight

Complete Your Digital Signage Solution
Add a network media player and digital signage software.

Media Players
- NMP-560 (RISC-based)
- NMP-640 (X86-based)

Software
- Friendlyway Composer Software
- Best Wave ***DisplayIt!*** Software
- ViewSonic® Siganage Manager Express



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Programs specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15737-00B-06/11] CD4232T-1

ViewSonic® See the difference®

For more product information, visit us on the web at ViewSonic.com